

State of Connecticut
Handicapped Parking Spaces and Signs
Statutes and Regulations

Connecticut General Statutes, Sec. 14-253a(h)

(h) Parking spaces designated for the handicapped on or after October 1, 1979, and prior to October 1, 2004, shall be as near as possible to a building entrance or walkway and shall be fifteen feet wide including three feet of cross hatch, or parallel to a sidewalk on a public highway. On and after October 1, 2004, parking spaces for passenger motor vehicles designated for the handicapped shall be as near as possible to a building entrance or walkway and shall be fifteen feet wide including five feet of cross hatch. On and after October 1, 2004, parking spaces for passenger vans designated for the handicapped shall be as near as possible to a building entrance or walkway and shall be sixteen feet wide including eight feet of cross hatch. Such spaces shall be designated by above grade signs with white lettering against a blue background and shall bear the words "handicapped parking permit required" and "violators will be fined". Such sign shall also bear the international symbol of access. When such a sign is replaced, repaired or erected it shall indicate the minimum fine for a violation of subsection (f) of this section. Such indicator may be in the form of a notice affixed to such a sign. On and after January 1, 2017, whenever such a sign is replaced, repaired or erected it shall bear the words "reserved parking permit required" and "violators will be fined", bear the symbol of access and indicate the minimum fine for a violation of subsection (f) of this section. Such indicator may be in the form of a notice affixed to such a sign.

ICC/ANSI A117.1-2009 Portion of the 2016 State Building Code

502 Parking Spaces

502.1 General. Accessible car and van parking spaces shall comply with Section 502.

(Amd) **502.2 Vehicle space size.** Parking spaces designated for persons with disabilities shall be as near as possible to a building entrance or walkway. Accessible automobile parking spaces shall be 15 feet in width including 5 feet of cross hatch. Accessible van spaces shall be 16 feet in width including 8 feet of cross hatch.

502.3 Vehicle Space Marking. Car and van parking spaces shall be marked to define the width. Where parking spaces are marked with lines, the width measurements of parking spaces and adjacent access aisles shall be made from the centerline of the markings.

EXCEPTION: Where parking spaces or access aisles are not adjacent to another parking space or access aisle, measurements shall be permitted to include the full width of the line defining the parking space or access aisle.

502.4 Access aisle. Car and Van Parking Spaces shall have an adjacent access aisle complying with Section 502.4.

(Amd) **502.4.1 Location.** Access aisles (cross hatch) shall adjoin an accessible route. Parking spaces for two cars or two vans may share a common access aisle. A car and van shall not share a common access aisle. Access aisles shall not overlap with the vehicular way. Parking spaces may have access aisles placed on either side of the car or van parking space. Van parking spaces that are angled shall have access aisles located on the passenger side of the parking space.

(Amd) **502.4.2 Width.** Access aisles (cross hatch) serving car parking spaces shall be 60 inches (1525

mm) minimum in width. Access aisles serving van parking spaces shall be 96 inches (2440 mm) minimum in width.

502.4.3 Length. Access aisles shall extend the full length of the parking spaces they serve.

502.4.4 Marking. Access aisles shall be marked so as to discourage parking in them. Where access aisles are marked with lines, the width measurements of access aisles and adjacent parking spaces shall be made from the centerline of the markings.

EXCEPTION: Where access aisles or parking spaces are not adjacent to another access aisle or parking space, measurements shall be permitted to include the full width of the line defining the access aisle or parking space.

502.5 Floor Surfaces. Parking spaces and access aisles shall comply with Section 302 and have surface slopes not steeper than 1:48. Access aisles shall be at the same level as the parking spaces they serve.

(Amd) **502.6 Vertical clearance.** Vertical clearance for accessible van parking spaces shall be in accordance with Section 1106.5 and 1106.5.1.1 of the 2012 International Building Code portion of the State Building Code.

(Amd) **502.7 Identification.** Accessible parking spaces shall be identified by above grade signs in accordance with Section 1110.1 of the 2012 International Building Code portion of the State Building Code.

502.8 Relationship to Accessible Routes. Parking spaces and access aisles shall be designed so that cars and vans, when parked, can not obstruct the required clear width of adjacent accessible routes.

2012 IBC Portion of the 2016 Connecticut State Building Code

SECTION 1106

PARKING AND PASSENGER LOADING FACILITIES

1106.1 Required. Where parking is provided, *accessible* parking spaces shall be provided in compliance with Table 1106.1, except as required by Sections 1106.2 through 1106.4. Where more than one parking facility is provided on a *site*, the number of parking spaces required to be *accessible* shall be calculated separately for each parking facility.

Exception: This section does not apply to parking spaces used exclusively for buses, trucks, other delivery vehicles, law enforcement vehicles or vehicular impound and motor pools where lots accessed by the public are provided with an *accessible* passenger loading zone.

(Add) **1106.1.1 Automobile accessible parking spaces.** Pursuant to subsection (h) of section 14-253a of the Connecticut General Statutes, parking spaces for passenger motor vehicles designated for persons who are blind and persons with disabilities shall be as near as possible to a building entrance or walkway and shall be 15 feet wide including 5 feet of cross hatch.

**TABLE 1106.1
ACCESSIBLE PARKING SPACES**

TOTAL PARKING SPACES PROVIDED	REQUIRED MINIMUM NUMBER OF ACCESSIBLE SPACES
1 to 25	1
26 to 50	2
51 to 75	3
76 to 100	4
101 to 150	5
151 to 200	6
201 to 300	7
301 to 400	8
401 to 500	9
501 to 1,000	2% of total
1,001 and over	20, plus one for each 100, or fraction thereof, over 1,000

(Amd) **1106.2 Groups R-2 and R-3.** At least two percent, but not less than one, of each type of parking space provided for occupancies in Groups R-2 and R-3, which are required to have Accessible, Type A or Type B dwelling or sleeping units, shall be accessible. Where parking is provided within or beneath a building, accessible parking spaces shall also be provided within or beneath the building. Exception: Private parking garages within or beneath the building that contain no more than two parking spaces, that are reserved for the exclusive use of a specific dwelling unit and are directly accessed from that dwelling unit are not required to be accessible.

1106.3 Hospital outpatient facilities. At least 10 percent, but not less than one, of care recipient and visitor parking spaces provided to serve hospital outpatient facilities shall be *accessible*.

1106.4 Rehabilitation facilities and outpatient physical therapy facilities. At least 20 percent, but not less than one, of the portion of care recipient and visitor parking spaces serving rehabilitation facilities specializing in treating conditions that affect mobility and outpatient physical therapy facilities shall be *accessible*.

(Amd) **1106.5 Van spaces.** For every six or fraction of six accessible parking spaces, at least one shall be a van-accessible parking space. Each public parking garage or terminal shall have a minimum of two van-accessible parking spaces complying with this section.

Exception: In Group R-2 and R-3 occupancies, van-accessible spaces located within private garages shall be permitted to have vehicular routes, entrances, parking spaces and access aisles with a minimum vertical clearance of 7 feet.

(Add) **1106.5.1 Van accessible parking spaces.** Pursuant to subsection (h) of section 14-253a of the Connecticut General Statutes, parking spaces for passenger vans designated for persons who are blind and persons with disabilities shall be as near as possible to a building entrance or walkway and shall be 16 feet wide including 8 feet of cross hatch.

(Add) **1106.5.1.1 Van access clearance.** Pursuant to subsection (i) of section 14-253a of the Connecticut General Statutes, each public parking garage or terminal shall have 8 feet 2 inches vertical clearance at a primary entrance and along the route to at least two parking spaces for passenger vans that conform to Section 1106.5.1 and that have 8 feet 2 inches of vertical clearance.

1106.6 Location. *Accessible* parking spaces shall be located on the shortest *accessible route* of travel from adjacent parking to an *accessible* building entrance. In parking facilities that do not serve a particular building, *accessible* parking spaces shall be located on the shortest route to an *accessible* pedestrian entrance to the parking facility. Where buildings have multiple *accessible* entrances with adjacent parking, *accessible* parking spaces shall be dispersed and located near the *accessible* entrances.

Exceptions:

1. In multilevel parking structures, van-accessible parking spaces are permitted on one level.
2. *Accessible* parking spaces shall be permitted to be located in different parking facilities if substantially equivalent or greater accessibility is provided in terms of distance from an *accessible* entrance or entrances, parking fee and user convenience.

1106.7 Passenger loading zones. Passenger loading zones shall be *accessible*.

1106.7.1 Continuous loading zones. Where passenger loading zones are provided, one passenger loading zone in every continuous 100 linear feet (30.4 m) maximum of loading zone space shall be *accessible*.

1106.7.2 Medical facilities. A passenger loading zone shall be provided at an *accessible* entrance to licensed medical and long-term care facilities where people receive physical or medical treatment or care and where the period of stay exceeds 24 hours.

1106.7.3 Valet parking. A passenger loading zone shall be provided at valet parking services.

1106.7.4 Mechanical access parking garages. Mechanical access parking garages shall provide at least one passenger loading zone at vehicle drop-off and vehicle pickup areas.

(Add) = Section added by the Connecticut Supplement. (Amd) = Section amended by the Connecticut Supplement.
(Del) = Section deleted by the Connecticut Supplement.